TE - TITAN S U P R E S S O R



TE-Titan Suppressor: Designed to Perform

The TE-Titan is made with Grade 5 Titanium (TiAI6V4) by using the cutting-edge additive manufacturing technology. This 3D printed suppressor is light-weight, extremely corrosion resistant and solid – both in terms of high tensile strength and toughness. The patented Inconell core of the QD Suppressor is designed to prevent sparks from its titanium body. The design also features an integrated heat shield that increases durability and prevents failure when shooting on the fully automatic mode.

Key Features

Quick Detach • Lightweight • High-heat resistance • High durability • Minimum back pressure •Low maintenance
Short added length in front of the barrel • Effective sound, recoil, and first-round • Flash Reduction





Military Suppressor

Made for military use on fully-automatic rifles. The TE-Titan enables an easy one-hand attach within seconds, making it the ideal choice for soldiers in combat situations. At an added front-end length of 150-230 mm/5.9 to 9 inches when mounted, it makes for a compact suppressor for calibers .223 Remington, .308 Winchester, .300 Winchester Magnum and .338 Lapua Magnum.



Technical Specifications:

Caliber : We can supply all caliber from.223 to .375 Weight : 200 – 450 grams/ 7 – 15.8 oz Length : 150 – 210 mm/ 5.9 to 8.2 inches External diameter : 45 – 55 mm/ 1.7 to 2.1 inches Sound reduction : 29 to 35 dB Length in front of the barrel : Depends on configuration





Test Results:

Suppressor	Caliber	Weight	dB Redu	ction
D45 150	.223 Rem	260 gm	With Inconell: 315 gram	29
D45 l210	.223 Rem	357 gm	With Inconell: 423 gram	35
D45 l210	.308 Win	350 gm	With Inconell: 420 gram	27
D55 I230	.308 Win	430 gm	With inconell: 490 gram	34
D55 I230	.338 Lapua	470 gm	With inconell: 560 gram	33

Price :

ltem no.	Text	Caliber	Threads
1132293	QD suppressor D45I=150 mm	.223	1⁄2"-28
1132615	QD suppressor D45I=210 mm	.223 and .308	¹ ⁄2"-28
1132615	QD suppressor D45I=210 mm	.223 and .308	1⁄2"-28
1132584	QD suppressor D55 I=230 mm	.308	M18x1
1132585	QD suppressor D55 I=230 mm	.338	M18x1
1132616	Recoil reducer adapter D55	Up to .338	M18x1
1160069	Compensator adapter D45	.223 and .308	On Request
1160068	Flash hider adapter D45	Up to .308	On request

Civil Suppressor

Made for use on shooting ranges and hunting purposes. At an added front-end length of 211 mm/ 8.3 inches when mounted, it makes for a compact suppressor for calibers .17 to .375.



Technical Specifications:

Caliber : We can supply all caliber from .17 to .375 Weight : 200-250 Gram/ 7 to 8.8 oz Length : 211 mm/ 8.3 External Diameter : 42 mm/1.65 inches Sound Reduction : 32Db Length in front of the barrel : 110 mm

Price :

ltem no.	Text	Caliber	Threads	Weight
1119755	Suppressor civil marked	.223	M14 x1	208 g
1119756	Suppressor civil marked	.223	1⁄2"-28	208 g
1119757	Suppressor civil marked	6 mm /6,5	M14 x1	250 g
1121224	Suppressor civil marked	6 mm /6,5	1⁄2"-28	250 g
1119758	Suppressor civil marked	.30 /7.62	M14 x1	255 g
1121226	Suppressor civil marked	.30 /7.62	1⁄2"-28	255 g
1121624	Suppressor civil marked	8 mm / .338	M14 x1	250 g
1119759	Suppressor civil marked	9.3	M14 x1	250 g
1119760	Suppressor civil marked	9.3	M15x1	250 g
1121625	Support ring in POM	All caliber	-	-
1160072	Suppressor front mounted	.223	M14 x1	170 g
1160072	Suppressor front mounted	.223	1⁄2"-28	170 g
1160073	Suppressor front mounted	6mm/6,5	M14 x1	170 g
1160074	Suppressor front mounted	.30	M14 x1	170 g
1160074	Suppressor front mounted	.30	1⁄2"-28	170 g

Please specify threads when ordering

Compensator IPSC (Comp Salen)





ltem no.	Text	Caliber	Threads
1160058	Comp. std. EDT*1	19mm	¹ / ₂ "-28
1160057	Comp. open EDT*1	19mm	¹ ∕₂" - 28
1155020	Comp. std. EDT*1	23mm	1⁄2"-28
1155019	Comp. open EDT*1	23mm	1⁄2"-28
1160060	Comp. std. Heckler&koch		M15x1
1160059	Comp. open Heckler&koch	.30 /7.62	M15x1
1160065	Comp. std/open 19/23	Others	On request

MADE IN NORWAY

Tronrud Engineering was founded by Ola Tronrud in 1977 and is a supplier of specialist machinery to the industry both at home and abroad. We assist our customers with the development of profi table industrial products and technical solutions. Our talented staff works closely with the customer througout the project process, from idea through design and construction to commissioning of pre-installed machines. Several thousand projects have been completed during the more than 30 years Trorud Engineering has existed.





Flyplassveien 21, N-3514 Hønefoss, Norway Phone +47 32 16 18 20 | mail@tronrud.no | nils.elsrud@tronrud.no www.tronrud.no